



## PRODUCT DATA SHEET

### NMX COMPRESSOR SERIES

**32,46,68,100,150,220**

#### DESCRIPTION & APPLICATION:

Formulated to provide reliable lubrication under conditions of moderate oxidation and thermal stress, these oils are produced using premium solvent-refined and hydrocracked base stocks. They are further enhanced with carefully selected additives that offer protection against wear, rust, oxidation, and foam formation.

- Excellent resistance to oxidation and heat degradation
- Minimal carbon deposit formation
- Strong anti-wear and extreme pressure (EP) performance
- Suitable for moderate-duty reciprocating, rotary, and screw air compressors operating at discharge temperatures up to 220°C
- Can also be used in vacuum pumps designed for air delivery above atmospheric pressure

#### **Performance Level**

DIN 51506 VD-L, IS 13256:1992 (Reaffirmed 2014) DAA and DAB Type.

#### SPECIFICATION:

PROPERTIES	NMX COMPRESSOR					
TYPICAL VALUES	32	46	68	100	150	220
Color	Clear, Bright Color					
Kinematic Viscosity @ 40°C, cSt	29-35	42-50	64-72	90-110	140-160	200-240
Viscosity Index, min.	100	100	100	100	100	100
Flash Point, COC, °C, min.	190	200	210	220	220	230
Pour Point, °C, max.	-12	-12	-9	-6	-6	-3

\*The specifications are subject to variations/ development / customization. PACKING: **26L, 50L, 55L, 210L**

\*Due to continual product research and development, the information contained herein is subject to change without notice.